


CRT ADAPTER



MODEL CR-21

ASSEMBLY WITH WIRES - 527-045-9 001



FITS CRT DIMENSIONS:

A = pin circle diameter	= 20.32 mm/0.800" nom.
a = angular pin spacing	= 25-5/7°
B = post diameter	= 11.5 mm/0.455" max.
C = keyway width	= 3.4 mm/0.135" max.
D = keyway depth	= 1.77 mm/0.070" max.
E = keyway width	= 1.83 mm/0.072" max.
R1 = outer keyway radius	= 26.24 mm/1.033" min.

WIRING SCHEME		
CRT SOCKET PIN	WIRE COLOR	NYLON RECEP- TACLE
1	BLK	1
2	YEL/RED	7
3	RED	5
4	WHT/RED	8
5	WHT/GRN	11
6	YEL/GRN	2
7	GRN	10
8	keyway	—
9	WHT	12
10	keyway	—
11	YEL/BLU	9
12	BLU	3
13	WHT/BLU	6
14	BRN	4



BK PRECISION

Maxtec International Corporation
6470 West Cortland Street
Chicago, Illinois 60635
Telephone: (312) 889-1448

Used with B & K-Precision Models: 467, 470

TUBE TYPE	HEATER VOLTAGE	TUBE TYPE	HEATER VOLTAGE	TUBE TYPE	HEATER VOLTAGE
24VABP22	6.3	A51-500X	6.3	A66-500X	6.3
560CXB22	6.3	A51-510X	6.3	A66-501X	6.3
560EZR22	6.3	A51-540X	6.3	A66-510X	6.3
560XCB22	6.3	A53JDH00X01	6.3	A66-540X	6.3
660AB22	6.3	A56-500X	6.3	A67-260X	6.3
660CB22	6.3	A56-510X	6.3	A67-560X	6.3
		A56-540X	6.3		

In order to keep your set-up chart up-to-date, it is recommended that you subscribe to the B & K-Precision chart mailing service. These mailings will occur in May and November of each year and will include all the tubes presently listed on your chart plus all new types of CRT's that have come out since the last mailing.

If you wish to take advantage of this service, contact:

B & K-PRECISION, Factory Service Department
 Maxtec International Corporation
 6470 West Cortland Street
 Chicago, Illinois 60635
 Telephone #: (312) 889-1448

For information on ordering a subscription.

